MOUNTING PROCEDURE

KIT LICENCE PLATE YAMAHA MT-09

YMT9104

KIT

X2 SPECIFIC BRACKET X1 THREADED THICKNESS

X2 SCREW 5X10 X4 SCREW 5X16 "ROUND HEAD"

X4 NUT DIAMETER 5 "AUTOLOCK" X4 WASHER DIAMETER 5 "LARGE"

X1 "X" LICENCE PLATE

WWW.BARRACUDAMOTO.COM

FIXING PROCEDURE:

- REMOVE THE SIDE PANELS, UNFIX THE ORIGINAL LICENCE PLATE AND APPROACH THE BARRACUDA SPECIFIC BRACKET UNDER THE UNDERTAIL FINDING THE FIXING POINTS;
- FIX THE LICENCE PLATE USING 4 SCREW 5X16, PUT THE THREARED THICKNESS IN CENTRAL POSITION RESPECT TO THE TWO BRACKET AND FIX WITH 2 SCREW 5X10 LIKE SHOW IN THE PICTURE;
- LOCK THE NUT E FIX THE SCREW 5X16
- MAKE THE SAME PROCEDURE WITH ALL PONITS OF FIXING OF BRACKET;
- APPLY THE "X" LICENCE PLATE TO THE TO THE SPECIFIC BRACKET;

